





Transfer in a blink of an eye

The ESD270C is equipped with the USB 3.1 Gen 2 interface with the support of UASP (USB Attached SCSI Protocol), providing transfer speeds of up to 520MB/s.



Compact and lightweight

Pack light! The credit-card size ESD270C, with mere 9.6mm in height, fits perfectly in your wallet or purse, and takes up little space in your briefcase. The antiscratch coating means the external SSD will look sharp even after all the miles. With a reflective black case, you'll be both savvy and stylish.



Expand storage in a flash

The ESD270C provides up to 2TB of storage capacity, ensuring you have plenty of space for backups, as well as storing your high-resolution images, 4K videos, and other media files!





Portable SSDs ESD270C Portable SSD

Features

- USB 3.1 Gen 2 interface with the support of UASP (USB Attached SCSI Protocol)
- 3D NAND flash
- Credit-card size fits perfectly in a wallet
- USB Type-C and USB Type-C to Type-A cable included
- Hardware-based 256-bit AES encryption secures your data



Transcend Elite

Transcend Elite is a data management software for external hard drives, USB flash drives and portable SSD products.

Specifications

Α	n	n		0	ro	n	0	0
$\overline{}$	μ	μ	$\overline{}$	a	10	11	\cup	$\overline{}$

Dimensions	77 mm x 55.7 mm x 9.6 mm (3.03" x 2.19" x 0.38")
Weight	35 g (1.23 oz)
Color	Black

Interface

USB Type	USB Type C to USB Type A / USB Type C to USB Type C
Connection Interface	USB 3.1 Gen 2 (USB 10Gbps)

Storage

Flash Type	3D NAND flash
Capacity	250GB / 500 GB / 1 TB / 2 TB

Operating Environment

Operating Temperature	0°C (32°F) ~ 70°C (158°F)
Operating Voltage	5V

Performance

Read Speed (Max.)	up to 520 MB/s
Write Speed (Max.)	up to 460 MB/s

Warranty

Certificate	CE / UKCA / FCC / BSMI / NCC / EAC / RCM
Warranty	Three-year Limited Warranty

Ordering Information

250GB	TS250GESD270C
500GB	TS500GESD270C
1TB	TS1TESD270C
2TB	TS2TESD270C

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.