



Card Readers RDE2

Transcend's CFexpress Type B Card Reader RDE2 is designed for use with CFexpress Type B memory cards. The USB 3.2 Gen 2x2 interface offers 20 Gbps transfer speeds, guaranteeing photography and cinematic experts excellent performance. It supports USB Type-A and Type-C devices, satisfying professionals' need to connect to different gadgets. The lightweight exterior and a non-slip silicone cover make the device highly portable and durable.



A trustworthy choice

Tailored to professional photographers using DSLR and advanced camcorders, Transcend's CFexpress Type B Card Reader RDE2 is designed for CFexpress Type B memory cards. This makes it the perfect choice for specialists. Boasting superior speeds and operational flexibility—as it supports both USB Type-A and Type-C computers, laptops, and mobile devices—the RDE2 card reader helps to make media production a snap!



20 Gbps blazing-fast transfer speed

The RDE2 card reader is equipped with a USB interface meeting the latest USB 3.2 Gen 2x2 specification. This means the device offers the eye-popping data transfer rate of 20 Gbps for smooth performance.

Notes:

1. The RDE2 card reader does not support XQD® cards.
2. 20 Gbps can only be achieved when the RDE2 card reader is connected to USB Type-C devices.



Maximum flexibility: USB Type-A and Type-C supported

Frustrated that your gadgets come with different port types? The RDE2 card reader solves that by providing USB Type-A and Type-C cables, allowing you to work more efficiently.



Card Readers RDE2

Features

- USB 3.2 Gen 2x2 interface
- 20 Gbps high transfer speed
- Exclusively for CFexpress Type B card
- Supports devices with USB Type-A or Type-C port
- Lightweight housing and non-slip silicone cover

Specifications

Appearance

Dimensions	75.9 mm x 53.5 mm x 14.7 mm (2.98" x 2.10" x 0.57")
Weight	82 g (2.89 oz)
Color	Space gray

Interface

USB Type	USB Type C to USB Type A / USB Type C to USB Type C
Connection Interface	USB 3.2 Gen 2x2 (USB 20Gbps)

Hardware

Card Reader Slot(s)	CFexpress Type B
---------------------	------------------

Operating Environment

Operating Temperature	0°C (32°F) ~ 70°C (158°F)
Operating Voltage	5V

Performance

Note	Speed may vary due to host hardware, software, usage, and storage capacity. To reach the maximum performance, the USB Type-C to Type-C cable shall be used, and please make sure your device supports USB 3.2 Gen 2x2 (USB 20Gbps).
------	--

Warranty

Certificate	CE / UKCA / FCC / BSMI / EAC / RCM
Warranty	Two-year Limited Warranty

System Requirement

Operating System	Microsoft Windows 7 or later macOS 10.2.8 or later Linux Kernel 2.6.30 or later
------------------	---

Compatibility

Memory Card Supported	CFexpress Type B
-----------------------	------------------

Ordering Information

OMB	TS-RDE2
-----	---------

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.