






## Vision in the dark

The DrivePro 620 includes one front camera and one rear camera. Both feature a high-sensitivity image sensor to capture high-resolution images in superb, rich color even in low light. Supporting 1440P 2K QHD recording at 60fps, the DrivePro 620 offers smooth footage as well as crisp still images.



# Dual camera recording, double the safety.

Packed with compact front and rear cameras, the DrivePro 620 monitors both the road ahead and behind simultaneously in ultra-high resolution, which means extra security for your journey. The 140° wide-angle view makes sure no details are missed. Plenty of smart functions make every journey safer.



#### Wi-Fi connectivity

The DrivePro 620 features Wi-Fi connectivity to connect it to the exclusive DrivePro App for real-time footage playback and download. When Wi-Fi is activated in the front camera, the rear camera will be automatically connected to Wi-Fi as well. This means ease of access to video evidence for reporting incidents to law enforcement and insurance companies without having to remove the memory card.





# Dual Camera Dashcam DrivePro 620

#### **Features**

- Dual camera recording for all-round protection
- Built-in Wi-Fi function for mobile live streaming
- Built-in battery prevents losing crucial images in the event of a power outage



#### DrivePro App

DrivePro App is designed for use with DrivePro dashcams featuring Wi-Fi connectivity. Stream videos and adjust settings from your mobile device, and download footage for on-the-go!



#### **DrivePro Toolbox**

DrivePro Toolbox helps you play and manage videos recorded on your DrivePro dashcam without installing any separate codecs.

## **Specifications**

| $\Lambda$ | n  | n |   | 0 | ra | n  | ce |
|-----------|----|---|---|---|----|----|----|
| $\neg$    | IJ | N | ㄷ | а | ıα | 11 | C  |

| Dimensions                   | Front Camera: 70.2 mm x 63.1 mm x 34.5 mm (2.76" x 2.48" x 1.36")<br>Rear Camera: 58.3 mm x 36 mm x 28.6 mm (2.3" x 1.42" x 1.12") |  |  |  |  |
|------------------------------|--|--|--|--|--|
| Weight                       | Front Camera: 82 g (2.89 oz)<br>Rear Camera: 40 g (1.41 oz)  |  |  |  |  |
| Interface                    |  |  |  |  |  |
| USB Type                     | micro USB to car lighter adapter   |  |  |  |  |
| Connection Interface         | USB 2.0  |  |  |  |  |
| Wi-Fi Protocol               | 802.11n  |  |  |  |  |
| Storage                      |  |  |  |  |  |
| Capacity                     | Two 32GB microSD card included   |  |  |  |  |
| Hardware                     |  |  |  |  |  |
| Display                      | 2.4" color TFT LCD (Front camera)  |  |  |  |  |
| Viewing Angle                | 140° (diagonal)  |  |  |  |  |
| Aperture                     | F/2.0  |  |  |  |  |
| Operating Environment        |  |  |  |  |  |
| Operating Temperature        | Front Camera: -20°C (-4°F) ~ 65°C (149°F)<br>Rear Camera: -20°C (-4°F) ~ 60°C (140°F)  |  |  |  |  |
| Input Voltage (Power cable)  | 12V ~ 24V  |  |  |  |  |
| Output Voltage (Power cable) | 5V / 2.4A  |  |  |  |  |
| Format                       |  |  |  |  |  |
| Resolution                   | 2K QHD 1440P   |  |  |  |  |
| Frame Rate                   | 60/30 fps  |  |  |  |  |
| Video Format                 | MP4 (H.264)  |  |  |  |  |
| Warranty                     |  |  |  |  |  |
| Certificate                  | CE / FCC / BSMI / NCC / MIC / KC / RCM / EAC / UKCA  |  |  |  |  |
| Warranty                     | Two-year Limited Warranty  |  |  |  |  |
| Package                      |  |  |  |  |  |
| Package Contents             | Front Camera / Rear Camera / Two 32GB microSD memory cards   |  |  |  |  |

# **Ordering Information**

| 32GB x2 | TS-DP620A-32G |
|---------|---------------|
|         |               |

/ Suction mount / Quick Start Guide

/ Car charger with dual USB ports / 8m USB Type-A to micro-USB cable / 4m USB Type-A to micro-USB cable / Adhesive mount

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.