



Accessories

HUB3

Ideal for use with Ultrabooks and thin-and-light laptops, Transcend's HUB3 transforms a single USB 3.1 Gen 1 port into four, instantly expanding the number of USB 3.1 Gen 1 devices you can connect to your computer at the same time. With the included power adapter, the HUB3 can supply high output currents of up to 2A via its dedicated fast charging port. This allows your mobile device to charge much quicker than using a standard USB port.



USB 3.1 Gen 1 interface

Compliant with the SuperSpeed USB 3.0 specification, Transcend's HUB3 provides data transfer rates up to 10 times faster than USB 2.0, allowing you to enjoy fast and efficient data transfer.



Highly portable

HUB3 is so small and compact that you can carry it around easily. You can also connect it to your laptop and PC with a USB cable.



Fast charging for mobile device

HUB3 provides 2A output current via the dedicated fast charging port, which allows your device to charge faster than using a standard USB port. Note: please use the lateral USB port to fast charge your device.



Accessories

HUB3

Features

- USB 3.1 Gen 1 interface (also compatible with USB 2.0)
- Provides 2A output current for fast charging your - mobile device
- Up to 10x faster than USB 2.0
- Supports USB Battery Charging specification v1.2
- LED indicates device insertion

Specifications

Appearance

| | |
|------------|---|
| Dimensions | 78.6 mm x 49.5 mm x 15 mm (3.09" x 1.95" x 0.59") |
| Weight | 44 g (1.55 oz) |

Interface

| | |
|------------------|---------------------------------------|
| Input Interface | USB 3.1 Gen 1/micro USB to USB Type A |
| Output Interface | USB Type-A x4 (USB 3.1 Gen 1) |

Operating Environment

| | |
|-----------------------|---------------------------|
| Operating Temperature | 0°C (32°F) ~ 60°C (140°F) |
|-----------------------|---------------------------|

| | |
|------|--|
| Note | Please be sure to connect both the USB port and the power adapter at the same time in order to use this product. |
|------|--|

Power

| | |
|---------------------|--|
| Power Supply (Max.) | 5V/2A from USB port 12V / 2A from power adapter |
|---------------------|--|

| | |
|------|--|
| Note | When the four USB ports are under heavy workloads, the hub may be unable to reach the maximum stated output current. |
|------|--|

Warranty

| | |
|-------------|-----------------------------|
| Certificate | CE/FCC/BSMI/KC/RCM/EAC/UKCA |
| Warranty | Two-year Limited Warranty |

System Requirement

| | |
|------------------|---|
| Operating System | Microsoft Windows 7 or later macOS 10.2.8 or later Linux Kernel 2.6.30 or later |
|------------------|---|

Ordering Information

TS-HUB3K