



Aiming at the new computer platforms with a Type-C USB port, such as Apple's 12-inch MacBook and Google's Chromebook Pixel 2, Transcend's RDC8 card reader with three slots can unleash the full potential of most of the flash cards, including SD cards, microSD cards, and CompactFlash cards. Equipped with USB 3.1 Gen 1 interface, Transcend's RDC8 is an ideal choice for fast and efficient data transfer from a flash card to a laptop with Type-C USB ports.



USB Type-C connector

Transcend's RDC8 card reader comes with a reversible USB Type-C connector for greater ease of use. You don't need to worry about plugging it in upside down. Transcend's RDC8 card reader is compatible with new laptops with a Type-C port, such as Apple's 12-inch MacBook and Google's Chromebook Pixel 2.



Blazing-fast transfer speeds

Taking full advantage of the USB 3.1 Gen 1 interface, Transcend's RDC8 card reader will unleash the full potential of your high-speed flash cards. In addition, the RDC8 has an LED indicator to show card insertion and data transfer activity.



Compact multifunctional card reader

Transcend's RDC8 card reader is equipped with three slots for SD memory cards, microSD memory cards, and CompactFlash cards, offering you a convenient way to transfer different types of digital files with one compact card reader. Note: The reader does not support simultaneous insertion of SD and microSD cards.





USB 3.1 Gen 1 Card Readers **RDC8**

Features

- · USB 3.1 Gen 1 interface
- · USB Type-C connector
- Multifunctional card reader with SD, microSD, and CompactFlash card slots
- Transfer high-resolution images and video recordings to your computer faster and more efficiently
- Download the RecoveRx data recovery software from Transcend's official website



RecoveRx software

Transcend's RDC8 card reader comes with RecoveRx software – a user-friendly application that allows you to conduct an in-depth search within your storage device for traces of erased data that can be recovered. Supported devices include memory cards, USB flash drives, digital music players, external hard drives, and solid state drives.

Specifications				
Appearance Dimensions (Max.)	67.6 mm x 45 mm x 15.2 mm (2.66" x 1.77" x 0.60")			
	,			
Weight (Max.)	32 g (1.13 oz)			
Color	Black			
Interface				
USB Type	micro USB to USB Type C			
Connection Interface	USB 3.1 Gen 1			
Hardware				
Card Reader Slot(s)	SD/microSD/CompactFlash			
Operating Environmen	2+			
Operating Environment Operating Temperature	0°C (32°F) ~ 70°C (158°F)			
	5V			
Operating Voltage				
Note	Simultaneous insertion of two cards not supported.			
Performance				
Note	Speed may vary due to host hardware, software, usage, and storage capacity.			
Warranty				
	65 (560 (B6) II II / 6			
Certificate	CE/FCC/BSMI/KC			
Certificate Warranty	Two-year Limited Warranty			
Warranty				
Warranty System Requirement	Two-year Limited Warranty			
Warranty System Requirement	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10			
Warranty System Requirement	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8			
Warranty System Requirement Operating System	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later			
Warranty System Requirement Operating System Compatibility	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later Linux Kernel 2.6.30 or later			
Warranty System Requirement Operating System	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later			
Warranty System Requirement Operating System Compatibility	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later Linux Kernel 2.6.30 or later			
Warranty System Requirement Operating System Compatibility	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later Linux Kernel 2.6.30 or later SDHC (UHS-I)/SDXC (UHS-I) microSDHC (UHS-I)/microSDXC (UHS-I) CompactFlash (UDMA7) This card reader will work with UHS-II cards, but only operates			
Warranty System Requirement Operating System Compatibility Memory Card Supported	Two-year Limited Warranty Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later Linux Kernel 2.6.30 or later SDHC (UHS-I)/SDXC (UHS-I) microSDHC (UHS-I)/microSDXC (UHS-I) CompactFlash (UDMA7)			

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.

TS-RDC8K2



USB 3.1 Gen 1 Card Readers Comparison	⊕ Transcend	(f) Transcend	(f) Transcend	© Transcend	® transcend ® transcend		
	RDC8	RDF9	RDF2	RDF8	RDF5		
Appearance							
Dimensions (Max.)		56 mm x 24 mm x 8.9 mm (2.20" x 0.94" x 0.35")					
Weight (Max.)	32 g (1.13 oz)	30.6 g (1.08 oz)	26 g (0.91 oz)	32 g (1.13 oz)	18 g (0.63 oz)		
Color	Black	Black	Black	Black/White	Black/White/Pink		
Interface			nicro USB to USB Typ		1.00 7		
USB Type	micro USB to USB Type C	USB Type-A					
Connection Interface	USB 3.1 Gen 1						
Hardware							
Card Reader Slot(s)	SD/microSD CompactFlash	SD/microSD CompactFlash	CFast	SD/microSD CompactFlash	SD/microSD		
Warranty							
Warranty	Two-year Limited Warranty						
Compatibility							
Memory Card Supported	SDHC (UHS-I)	SDHC (UHS-II)	CFast 2.0	SDHC (UHS-I)	SDHC (UHS-I)		
	SDXC (UHS-I)	SDXC (UHS-II)		SDXC (UHS-I)	SDXC (UHS-I)		
	microSDHC (UHS-I)	SDHC (UHS-I)		microSDHC (UHS-I)	microSDHC (UHS-I)		
	microSDXC (UHS-I)	SDXC (UHS-I)		microSDXC (UHS-I)	microSDXC (UHS-I)		
	CompactFlash (UDMA7) r			CompactFlash (UDMA7	7)		
		microSDXC(UHS-I)	`				
		mpactFlash (UDMA6 mpactFlash (UDMA7					
SD UHS-II	-	✓	-	-			
SD UHS-I and below	✓		-	✓			
microSD UHS-I and below	✓	✓	-	✓	~		
CompactFlash UDMA5 and below	~	✓	-	✓	-		
CompactFlash UDMA7 & UDMA6	✓	~	-	✓	-		
CFast 2.0 and below	-	-	~	-	-		

Note: Simultaneous insertion of two cards not supported.