



Body Cameras DrivePro™ Body 52

Transcend's DrivePro Body 52 body camera features a camera unit connected to the main unit by a flexible cable, allowing for a wide variety of attachment options. Tailor-made for law enforcement, private security, and other professionals, the DrivePro Body 52 is rugged and durable to withstand splashing water and shock. The camera features an Exmor™ image sensor to capture high-resolution images with extremely fine tonal gradation even in low light. With built-in Wi-Fi, the DrivePro Body 52 allows users to live-stream footage and snapshots to iOS and Android mobile devices.



Separate camera unit with high sensitivity image sensor

The DrivePro Body 52 is comprised of a main unit and a separate, compact camera unit, which can be securely mounted on uniforms and vests for more flexible wearing options. The camera features a wide 130° horizontal field of view, a large f/1.8 aperture, and an Exmor™ image sensor for high-resolution images with superb, rich color even in low light conditions.



Mounting accessories included

All necessary mounting accessories are included with the DrivePro Body 52. Officers can choose to use either the 360° rotating clip or Velcro holder to mount the camera unit on their uniform or jacket, and use the belt holster to carry the main unit on their duty belt.



Quick snapshot button

The DrivePro Body 52's quick snapshot button allows users to take photos while recording video simultaneously. During an incident, just reach up and discreetly press the snapshot button to capture photographic evidence on the spot.



Body Cameras

DrivePro™ Body 52

Features

- High sensitivity Exmor™ image sensor
- F/1.8 aperture and 130° viewing angle for clear and smooth 1080P recordings
- Built-in Wi-Fi function for live streaming
- Quick snapshot button
- 360° rotatable clip, Velcro holder and belt holster included

Specification

Appearance

Dimensions (Max.)	88.4 mm x 52.2 mm x 17.4 mm (3.48" x 2.06" x 0.68")
Camera Dimensions (Max.)	40 mm x 40 mm x 20.35 mm (1.57" x 1.57" x 0.80")
Weight (Max.)	84 g (2.96 oz)
Camera Weight (Max.)	64 g (2.26 oz)

Interface

USB Type	3.5mm plug to USB Type A
Connection Interface	USB 2.0

Storage

Capacity	32GB internal memory
----------	----------------------

Hardware

Viewing angle	130° (diagonal)
Aperture	F/1.8

Power

Battery Life (Fully Charged)	3.5 hour(s)
Power Supply (Max.)	Input: AC 100V-240V, 50-60Hz, 0.4A Output: DC 5V / 2A

Format

Resolution	Full HD 1080P
Frame Rate	30 fps
Video Format	MOV (H.264)

Operating Environment

Operating Temperature	-20°C (-4°F) ~ 65°C (149°F)
Storage Temperature	-25°C (-13°F) ~ 70°C (158°F)
IP Rating	IPX4

Warranty

Certificate	CE / FCC / BSMI / KC / NCC / MIC / EAC / RCM
Warranty	Two-year Limited Warranty

Ordering Information

32GB	TS32GDPB52A
------	-------------



DrivePro Body Toolbox



Transcend's DrivePro Body Toolbox is exclusively designed for the DrivePro Body series, featuring a user-friendly interface that allows users to securely manage recorded videos and snapshots on Windows PCs. In addition, users can adjust settings for both the toolbox and the DrivePro Body device, format the internal storage, and upgrade the body camera's firmware via the toolbox.

Body Cameras Comparison



DrivePro™ Body 60



DrivePro™ Body 30



DrivePro™ Body 52



DrivePro™ Body 20



DrivePro™ Body 10

Appearance

Dimensions (Max.)	95.9 mm x 52.2 mm x 24.9 mm (3.78" x 2.06" x 0.98")	95.9 mm x 52.2 mm x 27.6 mm (3.78" x 2.06" x 1.09")	88.4 mm x 52.2 mm x 17.4 mm (3.48" x 2.06" x 0.68")	88.4 mm x 52.2 mm x 19.4 mm (3.48" x 2.06" x 0.76")	88.4 mm x 52.2 mm x 19.6 mm (3.48" x 2.06" x 0.77")
Camera Dimensions (Max.)	61.3 mm x 22 mm x 22 mm (2.41" x 0.87" x 0.87")	-	40 mm x 40 mm x 20.35 mm (1.57" x 1.57" x 0.80")	-	-
Weight (Max.)	167 g (5.89 oz)	130 g (4.59 oz)	84 g (2.96 oz)	88 g (3.10 oz)	88 g (3.10 oz)
Camera Weight (Max.)	-	-	64 g (2.26 oz)	-	-
Interface					
USB Type	3.5mm plug to USB Type A	3.5mm plug to USB Type A	3.5mm plug to USB Type A	3.5mm plug to USB Type A	micro USB to USB Type A
Connection Interface	USB 2.0				
Storage					
Capacity	64GB internal memory	64GB internal memory	32GB internal memory	32GB internal memory	32GB
Hardware					
Viewing angle	130° (diagonal)	130° (diagonal)	130° (diagonal)	160° (diagonal)	130° (diagonal)
Aperture	F/2.8	F/2.0	F/1.8	F/2.8	F/2.8
Image Sensor	Exmor™	STARVIS™	Exmor™	Aptina™	STARVIS™
Infrared LEDs	-	✓	-	-	✓
Wi-Fi	✓	✓	✓	✓	-
Bluetooth	✓	✓	-	-	-
Microphone	✓	✓	✓	✓	✓
Vibration Alert	✓	✓	-	-	-
Buffering Mode	✓	✓	-	-	-
Event Recording	-	-	✓	✓	✓
Loop Recording	✓	✓	✓	✓	✓
Power					
Battery Life (Fully Charged)	10 hour(s)	12 hour(s)	3.5 hour(s)	3.5 hour(s)	5 hour(s)
Power Supply (Max.)	Input: AC 100V-240V, 50-60Hz, 0.4A Output: DC 5V / 2A				
Format					
Resolution	Full HD 1080P				
Frame Rate	30 fps	30/60 fps	30 fps	30 fps	30/60 fps
Video Format	MP4 (H.264)	MP4 (H.264)	MOV (H.264)	MOV (H.264)	MP4 (H.264)
Operating Environment					
IP Rating	IP67	IP67	IPX4	IPX4	IPX4
Warranty	Two-year Limited Warranty				

Note: Exmor/STARVIS is a trademark of Sony Corporation. Aptina is a trademark of Aptina Imaging Corporation.